

Game Changing Features

Front 90/90-12 **Tubeless Tyre** Every uneven

path will feel as flat as a batting pitch with Activa 6G's bigger front wheel

Change the game with Telescopic Suspension that helps you sail through those rough roads. It offers comfort and peace of mind to make your ride the best part of your day.





Hit it out of the park with the globally acclaimed eSP technology that helps in silent start, reduces friction and increases mileage by 10%[^].









Suspension

Silent Start with ACG

Powered by the globally acclaimed eSP technology which helps in silent start, the new Activa 6G is the match-winning hit you've been waiting for, Its ACG Starter Motor removes gear meshing, gear engagement noise and reduces maintenance.



10%[^] More Mileage

The winning combination of a completely new engine platform and Honda's globally acclaimed eSP technology delivers 10%[^] more mileage.



Engine Start/Stop Switch

Start and stop your scooter with just the press of a button anytime, anywhere for utmost convenience.



Multi Function Unit

One compact console ensures convenience of opening underseat storage & external fuel lid.



3-Step Rear Adjustable Suspension

Now customize your ride as per your comfort with the 3-step adjustable rear suspension.



Full Metal Body

No matter what condition you ride on, you can rely on Activa 6G's full metal body with confidence. Who knew facing a googly could be this easy!



LED DC Headlamp

The LED DC Headlamp gives riding irrespective of the



Programmed Fuel Injection

Sensor-based advanced PGM-FI system constantly injects optimum fuel resulting in efficient combustion which aids in consistent power output & higher mileage.



consistent illumination while acceleration, leaving everyone awestruck.











Other Honda Shield Products** Annual Maintenance Contract Road Side Assistance



Follow us on









Pearl Spartan Red

Technical Specifications+

1833 mm

697 mm

1156 mm

1260 mm

171 mm

692 mm

107 Kg

109.51 cc

47.0 mm

63.1 mm

PGM-Fi

10.0±0.2

Kick/Self

Automatic

Tubeless

Tubeless

90/90-12 54J

90/100-1053J

Drum - 130 mm

Drum - 130 mm

Loaded Hydraulic

3-Step Adjustable Spring

Under Bone

Telescopic

3.0 Ah

LED

Fan Cooled, 4 Stroke, SI Engine

5.73 kW @ 8000 rpm

8.79 N-m @ 5250 rpm

Viscous Paper Filter

5.3 L

Body Dimensions

Ground Clearance

Fuel Tank Capacity

Length

Width

Height

Wheel Base

Seat Length

Kerb Weight

Displacement

Max Net Power

Max Net Torque

Engine

Type

Bore

Stroke

Fuel System

Air Filter Type

Transmission Clutch Type

Tyres & Brakes

Tyre Size (Front) Tyre Size (Rear)

Tyre Type (Front)

Tyre Type (Rear)

Frame Type

Electricals

Headlamp

Battery

Front

Rear

Brake Type & Size (Front)

Brake Type & Size (Rear)

Frame & Suspension

Starting Method

Compression Ratio



Dazzle Yellow Metallic



Pearl Precious White



Matte Axis Grey Metallic